



KEDOJOINT GREY AND WHITE

MORTAR FOR TILE GROUTING CG1 CLASS

TECHNICAL DEFINITION.

KEDOJOINT is a cement base mortar for grouting on floor and wall interior and exterior tiling. Maximum joint width 6mm.

Available in grey and white.

COMPOSITION AND APPEARANCE.

Grey or white cement, sand, resin and various additives.

The resulting paste is light grey.

ACCEPTED SUBSTRATES.

All types of wall and floor substrates, interior and exterior, other than heated floors and wood panels.

COVERINGS.

Ceramic, porcelain, limestone, marble, terra cotta.

TECHNICAL CHARACTERISTICS.

- Mix working time: 5 h.
- Time before putting into service: 24 hours.
- Density: 1.6.

PACKING.

5 and 25 kg bags.

STORAGE.

6 months in unopened original packing protected from damp. mé.

APPLICATION

PRECAUTIONS.

DO NOT USE: In rooms requiring intensive cleaning and harsh products. In hot and dry weather (the temperature must be between 5 and 35°C).

PREPARATION OF SUBSTRATES BEFORE APPLICATION.

Tiling must have been laid 24 hours at least before the grouting is carried out. The joints must be dry and free of dust.

MIXING FACTOR.

Approximately 1.8 l of water per 5 kg bag (or 9 l. for 25 kg).

Allow the paste obtained to stand for 15 min.

APPLICATION.

Spread the mortar in the joints using a rubber squeegee and remove excess, preferably by pulling across the diagonal. Finish the grouting with a damp sponge and allow to set.

JOINT WIDTH.

Up to 6 mm.

CONSUMPTION.

Depends essentially on the width of the joints and the size of the tiles. The following table gives a few indicative coverage figures (in kg/m²).

Tile size (in cm)	2 mm joint	4 mm joint	6 mm joint
10 x 10	0,35	0,7	1,1
20 x 20	0,3	0,6	0,9
30 x 30	0,25	0,5	0,75
40 x 40	0,2	0,4	0,6

MORTAR FOR TILE JOINT GROUTING

KEDOJOINT is designed for easy grouting of all floor and wall tiling up to 6 mm width.

Only for surface areas not exposed to intense chemical aggression.

ADVANTAGES

- Waterproof joints.
- No cracking or crazing.
- Easy to apply.

APPLICATION TIP

For impeccable results, sprinkle with fine sand before complete setting of KEDOJOINT, then clean with a damp sponge.

AVAILABLE IN GREY AND WHITE

