



] PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Furrings (C type). Metal profile for producing the framework of ceilings, coverings and linings. The base of the furrings is used as a support for the boards.

Available lengths : from 45 -> 47

2.40m	2.60m	2.65m	2.70m
2.80m	3.00m	3.30m	5.30m

Nominal thickness:	0.57
Protection :	galva Z 140
Steel :	DX 51

] REFERENCES & PACKAGINGS

Référence	Article	Longueur (ml)	Longueur/botte	Longueur/palette	Gencode
A05630	45 Furring	2,40	10	600	3585501056307
A05327	45 Furring	2,70	10	600	3585501053276
A06019	45 Furring	2,80	10	600	3585501060199
A05108	45 Furring	3,00	10	600	3585501051081
A05109	45 Furring	5,30	10	600	3585501051098
A05319	47 Furring	2,40	10	600	3585501053191
A05101	47 Furring	2,60	10	600	3585501051012
A05502	47 Furring	2,65	10	600	3585501055027
A05102	47 Furring	2,70	10	600	3585501051029
A05246	47 Furring	2,80	10	600	3585501052460
A05103	47 Furring	3,00	10	600	3585501051036
A05104	47 Furring	3,30	10	600	3585501051043
A05107	47 Furring	5,30	10	600	3585501051074

] ADVANTAGES

- Pouncing.
- Classic and fast install

] REFERENCES TO TECHNICAL DOCUMENTS

- Standard NF411
- Standard NF EN 14195
- www.cstb.fr
- www.semin.com

] AREA OF APPLICATION

- Ceilings
- Linings
- Trim panel (Non-load-bearing partition inside a building over the entire height between floor and bottom of fixed ceiling and adding a lining to an existing wall. (DTU 25.41)

] INSTRUCTIONS FOR USE

1. Attach the furring to the hangers screwed to the wooden frame by turning it until hearing the "click".
2. Then screw the plasterboard onto the furrings.



DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Corner pieces
- Intermediate supports
- Pivot rod brackets
- Hangers
- Furring fittings