



SEMIN SOUS-COUCHE

PLASTERBOARD PRIMER

TECHNICAL DEFINITION

This general-purpose undercoat is suitable for indoor use to obtain a substrate ready to receive paint, wallpaper, wall coverings and every type of filler.

Allows subsequent removal of wallpaper or wall coverings without damage to the substrate.

Specially formulated for application to plasterboard.

Anti Flash Rust treated: blocks rust spots on concrete reinforcing or screw heads.

COMPOSITION AND APPEARANCE

Emulsion resin, calcium carbonate, rheological agent and various additives. The resulting paste is white and has a liquid consistency.

ACCEPTED SUBSTRATES

INDOOR WALLS AND CEILING:

- Plasterboard.
- Plaster.
- Plaster blocks.
- Concrete raw from formwork release.

COVERING

- Wallpaper.
- Paint.
- Wall coverings.
- All types of render.

DOCUMENTS TO CONSULT DTU 59.1

Note that DTU 59.1 requires the priming of certain substrates, in particular plasterboard.

TECHNICAL CHARACTERISTICS

- Density: 1.7
- Dry Matter: 65 %.
- pH: 7
- COV: < 1 g/l. (cat A/g – 30 g/l – 2010).

PACKING

25 kg pails.

STORAGE

18 months in unopened original packing protected from cold and extreme heat.

APPLICATION

PRECAUTIONS FOR USE

Do not apply when the temperature is less than 8° C.

For renovation, make sure that the primer does not soak through the previous covering.

PREPARATION OF SURFACES BEFORE APPLICATION

Indoor substrates must be in conformity with DTU 59.1, i.e., be clean, dry, hard, free of dust and any trace of release agent.

Wash and rinse old paint.

APPLICATION

It is possible to add up to 5 % water.

To be applied in a single coat using a roller, brush or gun. Clean tools in water.

DRYING TIME

- Dust free: 20 to 30 minutes.
- Dry: 1 to 2 hours.
- Dry-to-recoat: 24 hours

CONSUMPTION

6 to 8 m²/kg. 150 to 200 m² with 25 kg pail.

UNDERCOAT FOR PLASTERBOARD

The use of SEMIN SOUS-COUCHE before painting or applying wall coverings is a way of optimizing the quality of the substrate and avoiding damage to it when the coverings are subsequently removed.

ADVANTAGES

- High opacifying ability.
- Substantial saving on the number of coats of paint.
- Great whiteness.

APPLICATION TIP

To eliminate risk of peeling or blistering always apply SEMIN SOUS-COUCHE to a totally dry and dust-free substrate.

VOC Directive 2004/42/EC.
EU limit value for this product (cat A/g): 30 g/l. (2010).
This product contains a maximum of 1 g/l.

