



# SEM-PRO XXL

## WALLPAPER PASTE

### READY TO USE - HIGH-PERFORMANCE

### VINYL AND SPECIAL WALLPAPER, WALLPAPER AND NONWOVEN COVERINGS

#### TECHNICAL DEFINITION

SEM-PRO XXL is a high performance ready-to-use paste, reinforced with resin, for hanging vinyl wallpapers, raised patterned vinyl (VER) and special wallpapers (velvet, grained).

Suitable for use in the kitchen and bathroom. Transparent when dry. Does not stain.

#### COMPOSITION AND APPEARANCE

Starch based adhesive paste containing, cellulose ether, resin, water and preserving agents.

SEM-PRO XXL is a creamy whitish gel.

#### ACCEPTED SUBSTRATES

- Plasterboard.
- Plaster blocks.
- Concrete or cement render.

#### COVERING

- Vinyl papers.
- Relief patterned vinyl.
- Light textile coverings.
- Nonwoven textiles for painting.
- Special wallpapers (velvet, grained).

#### DOCUMENTS TO CONSULT DTU 59.4.

#### TECHNICAL CHARACTERISTICS

Density: Approximately 1.

#### PACKING

5 kg and 15 kg plastic pails.

#### STORAGE

6 months in unopened original packing protected from cold and extreme heat (storage temperature range between 0 and 30° C), 1 to 2 months once opened.

### APPLICATION

#### PRECAUTIONS FOR USE

The temperature during application and drying should be between 8 and 35° C.

#### PREPARATION OF SURFACES

Substrates must be sound, dry and free of dust, normally absorbent and must be in conformity with DTU 59.4. On absorbent surfaces, (plaster blocks, plasterboard), first apply our SEMIN SOUS COUCHE primer. Remove old wallpaper.

Sand, wash and rinse old paint. Strip any flaking paint.

On soft surfaces, apply our DURCIFOND hardener.

To help slide drops to match it may be advisable to size the substrate with diluted SEM-PRO XXL using 1 part paste to 3 or 4 parts water.

#### PASTING THE COVERINGS

Apply paste to the back of the covering, spreading it evenly and in sufficient amounts.

Allow to soak into the paper referring to the instructions of the maker (approximately 5 to 10 min). It is possible to paste up several lengths in advance, not allowing the paste to dry more than 40 minutes.

Fold back the ends of each length, bringing them end-to-end.

#### HANGING THE WALL-COVERINGS

Hang the length from the top of the wall and smooth out from top to bottom and from centre to sides. Use a sponge to mop up any excess adhesive and finish off the joins with a roller.

Clean up fresh paste stains using a damp sponge.

**CONSUMPTION** 200 g/m<sup>2</sup>.

### HIGH PERFORMANCE WALLPAPER PASTE

Thanks to the resins it contains, SEM-PRO XXL is recommended for pasting nonwoven coverings, special or vinyl base wallpapers and is ideal for wet rooms (kitchens, bathrooms).

#### ADVANTAGES

- Suitable for all types of wallpaper.
- Ready-to-use.
- Does not stain.

#### APPLICATION TIP

To allow them to stabilize, store your rolls of wallpaper in the room where they are to be hung at least 48 hours in advance.

