



SEMPRIM

INTERIOR

**High-quality interior acrylic primer.
Odourless.**

SUITABLE SUBSTRATES

All primed interior substrates, walls and ceilings.

INSTRUCTIONS FOR USE

PREPARATION OF SUBSTRATES

The substrate must be prepared according to the rules of DTU 59.1.

TOOLS

Brush, roller and airless spray gun (519 nozzle).

TOOLS CLEANING

With water.

YIELD

9 m² per liter.

DRYING (AT 23°C – 50% RH)

Dry time: 2 hours.

Dry-to-recoat time: 6 hours

PRECAUTIONS FOR USE

- Do not apply at a temperature lower than +8°C relative humidity higher than 70%.
- Do not apply to overheated substrates.
- Do not apply to damp substrates.

TECHNICAL INFORMATION

PACKAGING

Plastic buckets of 15 liters.

STORAGE

18 months in unopened packaging. Store away from frost.

WET ABRASION RESISTANCE

Standard NF EN 13300 : class 2

(loss of film thickness > 5µm and < 20 µm, after 200 cycles).

DRY EXTRACT (BY WEIGHT)

57 %

DENSITY

1.5 (standard EUR PL 004).

ADVANTAGES

- Anti flash-rust treatment
- Very strong adhesion
- Highly opaque
- Regulates substrate porosity

Regulations in force :

Standard AFNOR T 36005

FAMILY I – CLASS 7b2.

Safety :

Aqueous phase product,
not subject to labelling.

Emissions in indoor air (according to ISO 16000) :

This product contains less
than 1g/l of VOCs.

