

SEM PRIM&FINISH

INTERIOR



Alkyd resin and water-based acrylic primer.

SUITABLE SUBSTRATES

All dry and sound indoor substrates with moisture between 6 to 16%. Plaster, plaster boards, wood, particleboard, old paintwork and any substrate with PH<9 (non-alkaline). Note: Dilute the first coat 1 to 3% for plaster substrates

INSTRUCTIONS FOR USE

PREPARATION OF SUBSTRATES

The substrate must be prepared according to the rules of DTU 59.1.

TOOLS

Roller and airless spray pump.

TOOLS CLEANING

With water.

YIELD:

Approximately 10-12 m² per liter.

DRYING (AT 23°C – 50% RH)

Dry time : 1 to 2 hours,
Dry-to-recoat time : 4 hours

PRECAUTIONS FOR USE

- Do not apply at a temperature lower than 8°C and above 35°C and relative humidity higher than 70%.
- Do not apply to overheated substrates.
- Do not apply to damp substrates.

TECHNICAL INFORMATION

PACKAGING

15 liters buckets.

STORAGE

18 months in unopened packaging. Store away from frost.

DRY EXTRACT (BY WEIGHT)

57 %

DENSITY

1,58 (standard EUR PL 004).

ADVANTAGES

- 2 in 1 primer
- Very easy application
- Taut, attractive look
- Excellent adhesion
- 2 layers can be applied in 1 day

Regulations in force :

Standard AFNOR T 36005
FAMILY I – CLASS 7b2/4a.

Safety :

Aqueous phase product,
not subject to labelling.

Emissions in indoor air (according to ISO 16000) :

This product contains max.
2 g/l of VOCs.

