



BETON HAFTGRUND

PRIMER FOR SMOOTH OR IMPERMEABLE SUBSTRATES

TECHNICAL DEFINITION

Ready-to-use, solvent-free adhesive primer for smooth or hardly porous substrates, for interior and exterior use.

BETON HAFTGRUND allows to achieve an adhesive bridge between such substrates and certain cement- or plaster-based products with a relatively low bond.

BETON HAFTGRUND also allows to regulate the porosity of heterogeneous substrates (presence of several materials of different nature).

APPEARANCE

Pink, ready-to-use primer with visible grain. Paint-like consistency.

SUITABLE SUBSTRATES

Can be applied onto interior and exterior walls, and also onto ceilings.

- Smooth cast-in-place concrete.
- Self-levelling concrete.
- Old paintwork.
- Old painted fibreglass coverings.

COVERINGS


Once completely dry, BETON HAFTGRUND can be covered with all types of product (cement-based, plaster-based, ready-to-use), in particular bonding compounds for lining and traditional plaster (for manual or machine application).

PACKING

5 and 20 kg pails.

STORAGE

12 months in unopened original packing protected from frost and high heat.



APPLICATION

PRECAUTIONS FOR USE

Rehomogenize before use. Do not dilute.

Working and drying temperature must range between 8 and 35° C. Do not apply onto a damp surface.

PREPARATION OF SUBSTRATES BEFORE APPLICATION

The substrate must comply with DTU 59.1, i.e. be clean, dry, free of dust and of any trace of stripping oil.

BETON HAFTGRUND is not a surface hardener. Therefore, a primer such as PRIM-SM must be applied beforehand to any soft substrate.

APPLICATION METHOD

BETON HAFTGRUND is to be applied using a brush or a woollen roller.

Apply a liberal coat onto the substrate and allow to dry before covering.

The drying time will depend on the substrate and ambient conditions. As a general rule, allow for approximately 6 hours.

CONSUMPTION

Approximately 300 g/m².

PRIMER FOR SMOOTH OR IMPERMEABLE SUBSTRATES

BETON HAFTGRUND is a ready-to-use, solvent-free adhesive primer for smooth or hardly porous substrates, for interior and exterior use.

ADVANTAGES

- **BETON HAFTGRUND** makes you feel more secure in case you have doubts about the substrate.
- For the lining of a smooth substrate, **BETON HAFTGRUND** allows bonded application and therefore allows to compensate for plumb defects, which is not the case with mechanical attachment methods.

APPLICATION TIP

Rehomogenize carefully before use.

Do not dilute.

Check the adhesive power of the substrates **BETON HAFTGRUND** is to be applied to.

VOC Directive 2004/42/EC.
EU limit value for this product (cat A/g): 30 g/l. (2010).
This product contains a maximum of 5 g/l.

