



] PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Fine, lightweight and flexible tape, made of polyethylene foam with closed cells.
FUNCTION : Expansion joint between screed and wall.
Essential for making a liquid screed.

| | | |
|--|---|---|
| Trade name | Product name | Peripheral Tape 150mm x 25m |
| Product dimensions | Thickness (in mm) | 5 |
| | Width (in mm) | 150 |
| | Length (in m) | 25 |
| | Weight (in kg) | 0.37 |
| Material | Polyethylene foam | |
| Consumption | Average consumption (per m) | 1 |
| Install information: all products | Unit pack : height (in cm) | 105 |
| | Unit pack : width (in cm) | 41 |
| | Unit pack : length (in cm) | 41 |
| | Unit pack : weight (in kg) | 2.59 |
| | Number of products / parcels (in items) | 7 |
| The product | Average density | 370g/roll |
| | Stabilisation humidity | 0.05 kg/m ² max |
| | Dimensional variations | without |
| | Compressibility | 7.1% |
| | Reaction to fire | Flammability class according to standard EN 13501:F |
| | Emission of formaldehyde | No formaldehyde in its production |

] ADVANTAGES

- Removes the negative effects of thermal expansion
- Reduces the transmission of noise and vibrations from the floor to the peripheral walls
- Prevents the formation of a thermal bridge between the floor and the walls
- Prevents water, cement, concrete leaks into the walls, spread industrial floors, heated floors and floating floors
- Can be used to adjust unevenness in the floor.

] AREA OF APPLICATION

- Is applied before laying a cement screed on the angle formed by the floor and the partitions.

] INSTRUCTIONS FOR USE

Apply between the partition and the floor by stapling it or gluing the peripheral tape after having folded it.

] REFERENCES & PACKAGINGS

- Product reference : A05717
- Barcode : 3585501057175
- Packaging : 7 rolls per blister pack

] REFERENCES TO TECHNICAL DOCUMENTS

- DTU 26.2 P1-2
- Customs nomenclature: 39219090

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Facilis adhesive mortar 25 kg

PERIPHERAL TAPE 150mmx25ml