



] PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

For bonding difficult areas on all media. Neutral mastic glue, a compound based on hybrid polymers with permanent elasticity and flexible bonding. Manufactured according to the ISO 11600G standard class 25HM. Solvent and isocyanate free.

Trade name	Product name	Special vapour barrier mastic glue
Dimensions du produit	Height (in mm)	230
	Width (in mm)	50
	Length (in mm)	50
	Weight (in kg)	0.5
Material	Compound based on hybrid polymers	
Consumption	Average consumption (per m ²)	-
	Average consumption (per m)	-
Install information : all products	Unit pack : type	carton
	Unit pack : height (in cm)	25
	Unit pack : width (in cm)	25
	Unit pack : depth (in cm)	25
	Unit pack : weight (in kg)	12.5
	Number of products / parcels (in items)	25
The product	Hardening system	By humidity
	Hardening speed	2,5 to 3mm per 24hrs (at T=23°C and 50% HR)
	Formation of skin	+/- 35 min (at T=23°C and 50% HR)
	Specific weight :	+/- 1,48g/mL
	Shore A	35 (+/- 5)
	Maximum admissible movement of joint	25%
	Tension 100% elasticity	0.8 N/mm ²
	Tensile strength	1.1 N/mm ²
	Elasticity on breaking	+/- 230%
	Shear strength	1.444 N/mm ²
Resistance to temperatures	-40°C à +90°C	
Couleur	Light grey	

] ADVANTAGES


- Very good resistance to humidity
- Insensitive to freezing
- Non-corrosive

] AREA OF APPLICATION

- Sealing and finishing of the difficult areas.
- Seals the peripheral edge of the airtight film: Semin vapour barrier
- Excellent adhesion without primer to materials : concrete, plaster, stone, filler, wood, metal, etc.

] INSTRUCTIONS FOR USE

The mastic glue is applied over the entire edge of the vertical and horizontal walls including the junction with the floor. Apply a continuous bead of mastic of 6-8mm and lay the vapour barrier protective film delicately as quickly as possible (15 mins max). The mastic combines the benefits of a double-sided adhesive tape with the advantages of a reactive adhesive system.



DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Vapour barrier : Used for affixing vapour protection.



REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature: 39100000
- ISO 11600G class 25HM.
- ISO 1183
- ISO 868
- ISO 8339-40
- DIN 53283

CONDITIONS FOR USE

- The substrates must be clean, dry,
- Dust-free and degreased.
- Cleaning: in water before drying.
- Storage: 12 months away from the cold and intensive
- Heat in the original unopened packaging.

REFERENCES & PACKAGINGS

- Product reference : A04919
- Barcode : 3585501049194
- Packaging : 25 cartridges per carton.
1200 cartridges per pallet. (One cartridge = 290ml)

PRECAUTIONS FOR USE

- Do not use below 5°C.
- Keep out of reach of children.
- Contains : Bis (1,2,2,6,6-pentamethyl-4-piperidyl sebacaat)-methyl (1,2,2,6,6-pentamethyl-4-piperidyl sebacaat)-N-beta-(aminoethyl)-gammaaminopropyl-trimethoxysilaan.
- May produce an allergic reaction.

MASTIC GLUE SPECIAL VAPOUR BARRIER